

http://www.amd.com/
Visit Advanced Micro Devices web site to learn about their latest products, obtain data sheets and literature.

AMD Literature Support: 1-800-222-9323
To obtain literature, call Advanced Micro Devices Literature Support.

AMD Customer Support: (408) 749-5703
To obtain technical support, call Advanced Micro Devices Customer Support. Voice support is available 8:00 AM to 5:00 PM Pacific Time.

EPROMs

Mfr.'s Type*		Organization	Access Time (ns)	Temperature Range (°C)	No. of Leads
Windowed CERDIP	PDIP (OTIP)				
AM27C64-90DC	—	8 K × 8	90	0 to +70	28
AM27C64-120DC	AM27C64-120PC	8 K × 8	120	0 to +70	28
AM27C64-150DC	AM27C64-150PC	8 K × 8	150	0 to +70	28
AM27C64-200DC	AM27C64-200PC	8 K × 8	200	0 to +70	28
AM27C128-90DC	—	16 K × 8	90	0 to +70	28
AM27C128-120DC	AM27C128-120PC	16 K × 8	120	0 to +70	28
AM27C128-150DC	AM27C128-150PC	16 K × 8	150	0 to +70	28
AM27C128-200DC	AM27C128-200PC	16 K × 8	200	0 to +70	28
AM27C256-55DC	—	32 K × 8	55	0 to +70	28
AM27C256-70DC	—	32 K × 8	70	0 to +70	28
AM27C256-90DC	—	32 K × 8	90	0 to +70	28
AM27C256-120DC	AM27C256-120PC	32 K × 8	120	0 to +70	28
AM27C256-150DC	AM27C256-150PC	32 K × 8	150	0 to +70	28
AM27C256-200DC	AM27C256-200PC	32 K × 8	200	0 to +70	28
AM27C512-70DC	AM27C512-70PC	64 K × 8	70	0 to +70	28
AM27C512-90DC	AM27C512-90PC	64 K × 8	90	0 to +70	28
AM27C512-120DC	AM27C512-120PC	64 K × 8	120	0 to +70	28
AM27C512-150DC	AM27C512-150PC	64 K × 8	150	0 to +70	28
AM27C512-200DC	AM27C512-200PC	64 K × 8	200	0 to +70	28
AM27C010-70DC	—	128 K × 8	70	0 to +70	32
AM27C010-90DC	AM27C010-90PC	128 K × 8	90	0 to +70	32
AM27C010-120DC	AM27C010-120PC	128 K × 8	120	0 to +70	32
AM27C010-200DC	AM27C010-200PC	128 K × 8	200	0 to +70	32
AM27C020-70DC	—	256 K × 8	70	0 to +70	32
AM27C020-90DC	—	256 K × 8	90	0 to +70	32
AM27C020-120DC	AM27C020-120PC	256 K × 8	120	0 to +70	32
AM27C020-150DC	AM27C020-150PC	256 K × 8	150	0 to +70	32
AM27C040-90DC	AM27C040-90PC	512 K × 8	90	0 to +70	32
AM27C040-120DC	AM27C040-120PC	512 K × 8	120	0 to +70	32
AM27C040-150DC	—	512 K × 8	150	0 to +70	32
AM27C040-200DC	—	512 K × 8	200	0 to +70	32

*Also available in the 32 lead, PLCC (JC) package.

5 V Flash Embedded Algorithms, 1 Million Cycle Endurance

AM29F010 Series

Mfr.'s Type		Organization	Access Time (ns)	No. of Leads
PLCC	TSOP			
AM29F010-45JC	AM29F010-45EC	128 K × 8	45	32
AM29F010-70JC	AM29F010-70EC	128 K × 8	70	32
AM29F010-90JC	AM29F010-90EC	128 K × 8	90	32
—	AM29F010-90PC*	128 K × 8	90	32
—	AM29F010-120PC*	128 K × 8	120	32

AM29F040B Series

Mfr.'s Type		Organization	Access Time (ns)	No. of Leads
—	—			
AM29F040B-55JC	—	512 K × 8	55	32
AM29F040B-70JC	AM29F040B-70EC	512 K × 8	70	32
AM29F040B-90JC	AM29F040B-90EC	512 K × 8	90	32
AM29F040B-120JC	AM29F040B-120EC	512 K × 8	120	32
—	AM29F040B-120PC*	512 K × 8	120	32
AM29F040B-150JC	—	512 K × 8	150	32

*PDIP package.

AM29F400B Series

Mfr.'s Type		Organization	Access Time (ns)	No. of Leads
TSSOP	SOP			
AM29F400BB-70EC	AM29F400BB-70SC	512 K × 8/256 K × 16	70	48/44
AM29F400BB-90EC	AM29F400BB-90SC	512 K × 8/256 K × 16	90	48/44
AM29F400BB-120EC	AM29F400BB-120SC	512 K × 8/256 K × 16	120	48/44
AM29F400BT-120EC	AM29F400BT-120SC	512 K × 8/256 K × 16	120	48/44
AM29F400BB-150EC	AM29F400BB-150SC	512 K × 8/256 K × 16	150	48/44

AM29F800B Series

Mfr.'s Type		Organization	Access Time (ns)	No. of Leads
—	—			
AM29F800BB-90EC	AM29F800BB-90SC	1 M × 8/512 K × 16	90	48/44
AM29F800BT-90EC	—	1 M × 8/512 K × 16	90	48/44
AM29F800BB-120EC	AM29F800BB-120SC	1 M × 8/512 K × 16	120	48/44
AM29F800BT-120EC	AM29F800BT-120SC	1 M × 8/512 K × 16	120	48/44

AM29F016B Series

Mfr.'s Type		Organization	Access Time (ns)	No. of Leads
—	—			
AM29F016B-75EC	—	2 M × 8	70	48
AM29F016B-120EC	—	2 M × 8	120	48
AM29F016B-150EC	—	2 M × 8	150	48

Top (T) or bottom (B) boot sector configuration.

Drivers and Receivers

Mfr.'s Type			Description	No. of Tx	No. of Rx	Temperature Range (°C)	No. of Leads
SOIC	PDIP	PLCC					
—	AM26LS30PC	AM26LS30JC	Dual Differential RS-422 Line/Quad Single Ended RS-423 Line Driver	2	0	0 to +70	16/20
AM26LS31SC	AM26LS31PC	—	Quad High Speed Differential Line Driver RS-422	4	0	0 to +70	16
—	AM26LS32PC	—	Quad Differential Line Receiver RS-422/RS-423	0	4	0 to +70	16/20
—	AM26LS33PC	—	Quad Differential Line Receiver	0	4	0 to +70	16

http://www.xicor.com/
Visit Xicor's web site to learn about their latest products, to obtain data sheets and literature.

Xicor's Customer Support Center: (408) 432-8888 ext. 2020
To obtain technical support, call the technical support center. Voice support is available 8:00 AM to 5:00 PM Pacific Time.

Digitally Controlled Potentiometers — XDCP

Mfr.'s Type	No. of Taps	Interface	V _{CC} (Volts)	Signal Range (Volts)	I _{CC} (mA)	I _{SA} (µA)	Resistance Values	No. of Leads	Features
X9312WP	100	U/D, INC	4.5-5.5	0-15	3.0	1000	1/10/100 K	8	Single XDCP Linear Taper
X9313WP	32	U/D, INC	3.0-5.5	±5	3.0	500	1/10 K	8	Single XDCP Linear Taper
X9511WP	32	U/D, INC	4.5-5.5	±5	3.0	500	1/10 K	8	Pushpot — Push Button Control 32 Tap Linear Taper
X9C102S	100	U/D, INC	4.5-5.5	±5	3.0	500	1 K	8	Single XDCP Linear Taper
X9C103S	100	U/D, INC	4.5-5.5	±5	3.0	500	10 K	8	Single XDCP Linear Taper
X9C104S	100	U/D, INC	4.5-5.5	±5	3.0	500	100 K	8	Single XDCP Linear Taper
X9C503S	100	U/D, INC	4.5-5.5	±5	3.0	500	50 K	8	Single XDCP Linear Taper
X9C503P	100	U/D, INC	4.5-5.5	±5	3.0	500	50 K	8	Single XDCP Linear Taper

Same Day Shipments For Product In Stock

ALLIED ► 793